

Steel Pipe Specifications Schedule 80

Manufactured per ASME B36.10

All weights and dimensions are nominal.

Extra Strong (XH) Schedule 80						
Nominal Size (IPS)	Diameter External (Inches)	Diameter Internal (Inches)	Wall Thickness (Inches)	Weight Per Foot Plain Ends (Pounds)	Internal Area (Sq. In.)	GPM at 10 ft/sec (Velocity)
1/8"	.405	.215	.095	.314	.036	1.1
1/4"	.540	.302	.119	.535	.072	2.2
3/8"	.675	.423	.126	.738	.141	4.4
1/2"	.840	.546	.147	1.087	.234	7.3
3/4"	1.050	.742	.154	1.473	.433	13.5
1"	1.315	.957	.179	2.171	.719	22.4
1-1/4"	1.660	1.278	.191	2.996	1.283	40.0
1-1/2"	1.900	1.500	.200	3.631	1.767	55.0
2"	2.375	1.939	.218	5.022	2.953	92.0
2-1/2"	2.875	2.323	.276	7.661	4.238	132.0
3"	3.500	2.90	.300	10.25	6.605	206.0
3-1/2"	4.000	3.364	.318	12.51	8.888	277.0
4"	4.500	3.826	.337	14.98	11.50	358.0
5"	5.563	4.813	.375	20.78	18.19	567.0
6"	6.625	5.761	.432	28.57	26.07	812.0